

MAINTENANCE

Window hardware

Introduction

Radisson Industries strongly recommends that customers clean and lubricate the window hardware at least 1 time per year, or as needed. Regular maintenance of the hardware parts will help extend the useful life, and to maintain the smoothness of operation.

Cleaning

Step 1

Use a soft cloth dampened with fresh water to clean exposed surfaces of the hardware.

Step 2

To remove the toughest stains, and to get rid of salt or grease deposits, it is recommended to use a soft mild soap. However, it is very important to always rinse the cleaned area with fresh water to avoid having soap residue on surfaces. This could alter the finish of the materials in the long term.

Lubrication

Step 1

Make sure that the parts to be lubricated are clean, dry, and free of impurities before applying the lubricant. Use an air spray can, if necessary, to remove dust.

Step 2

Because of its sealing properties, lithium based grease spray (Jigg-A-Loo, WD-40 etc.) is strongly suggested to lubricate the hardware mechanisms.

Step 3

While operating the devices, apply the lubricant on the rails and the inner parts of the various components and mechanisms. This will allow the product to adequately penetrate, and increase its efficiency.



Vinegar, abrasive, acidic, citrus based cleaners, and gasoline are to be avoided completely. They could alter or damage the surfaces and finishes permanently.

For this reason, RADISSON INDUSTRIES strongly advises against the use of chemicals on its products.
(See detailed document «TS-03-Hydrochloric Acid-EN_1.1.pdf»)